

## TRIAC BT Plastic welding set




Plastic welding made easy

- Light and easy to handle
- Ergonomic handle for welding without strain
- Electronically protected heating element
- Integral precision nozzle
- Built-in start up protection in case of power interruption
- Complete kit including accessories tool box and spare heating element



### SPECIFICATIONS




136.939

Voltage	V~	230
Power consumption	W	1600
Temperature	°C	20 – 700
Air flow (20°C)	l/min	230
Noise emission level LpA	dB	67
Size (L x W x H)	mm	370 × 90, handle 56Ø
Weight	kg	1.0
Marking of conformity		
Approval mark		
Certification scheme		CCA, CB
Protection class II		

136.943

Voltage	V~	120
Power consumption	W	1550
Temperature	°C	20 – 700
Air flow (20°C)	l/min	230

## Plastic Welding &gt; Hand tools &gt; TRIAC BT Plastic welding set

Noise emission level LpA	dB	67
Size (L x W x H)	mm	370 × 90, handle 56Ø
Weight	kg	1.0
Marking of conformity		
Approval mark		
Certification scheme		CCA, CB
Protection class II		

## ACCESSORIES



Tacking nozzle push-fit on tubular nozzle  $\varnothing$  5 mm

106.996 - Tacking nozzle, push-fit on tubular nozzle  $\varnothing$  5mm



Speed welding nozzle 3, 4, 5 mm push-fit on tubular nozzle  $\varnothing$  5 mm

106.989 - Speed welding nozzle 3 mm, push-fit on tubular nozzle  $\varnothing$  5 mm

106.990 - Speed welding nozzle 4 mm push-fit, on tubular nozzle  $\varnothing$  5 mm

106.991 - Speed welding nozzle 5 mm, push-fit on tubular nozzle  $\varnothing$  5 mm



Speed welding nozzle 5.7, 7 mm push-fit on tubular nozzle  $\varnothing$  5 mm


106.992 - Speed welding nozzle 5.7 mm, push-fit on tubular nozzle  $\varnothing$  5 mm

106.993 - Speed welding nozzle 7 mm, push-fit on tubular nozzle  $\varnothing$  5 mm



Heating element 136.916

136.916 - Heating element 136.916



Tool box 116.586

116.586 - Tool box