

DIODE S with MINOR



To the product

Technical data

Voltage	100 V; 120 V; 230 V	
Frequency	50/60 Hz	
Power	1500-1700 W	
Temperature	20-600 °C	68.0-1112.0 °F
Temperature setting stepless	Yes	
Stepless air volume adjustment	No	
Static pressure	5000 Pa	0.72 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in; M14	
Length	256.0 mm	10.07 in
Device diameter	57 mm	2.24 in
Handle diameter	40 mm	1.57 in
Power cable length	3.0 m	9.84 ft
Air hose length	1.5-3.0 m	4.92-9.84 ft
Noise emission level	67 dB (A)	
Approvals	CB Certification; CE; UKCA	
Protection class	II	
Country of origin	CH	



DIODE S with MINOR

Product items

101.440	DIODE S / MINOR, 230V/1700W, 3m, EU plug
101.441	DIODE S / MINOR, 230V/1700W, 1.5m, EU plug
101.447	DIODE S / MINOR, 120V/1700W, US plug
101.449	DIODE S / MINOR, 100V/1500W, JP plug
108.869	DIODE S / MINOR, 230V/1700W, 3m, M14, EU plug
108.870	DIODE S / MINOR, 230V/1700W, 1.5m, M14, EU plug
136.241	DIODE S / MINOR, 230V/1700W, CN plug