

FORTE S3

Powerful hand tool for shrinking even in the most confined spaces.

- Powerful pallet-shrinking tool
- Uniform shrinkage
- May be used in the most confined spaces
- Integrated tool stand



SPECIFICATIONS

FORTE S3 3x230 V

Voltage	V~	3 x 230
Power consumption	W	10000
Frequency	Hz	50 / 60
Temperature	°C	650
Air flow (20°C)	l/min	1000
Pressure static	Pa	1200 (12 mbar)
Noise emission level LpA	dB	76
Size (L x W x H)	mm	390 x 132 x 215
Weight	kg	5.2 (with 10 m cord)

Marking of conformity



Approval mark



Certification scheme

CCA




Protection class II






FORTE S3 3x400 V

Voltage	V~	3 x 400
Power consumption	W	10000

Plastic Welding > Hand tools > FORTE S3

Frequency	Hz	50 / 60
Temperature	°C	650
Air flow (20°C)	l/min	1000
Pressure static	Pa	1200 (12 mbar)
Noise emission level LpA	dB	76
Size (L x W x H)	mm	390 x 132 x 215
Weight	kg	5.2 (with 10 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		

FORTE S3 3x440 V

Voltage	V~	3 x 440
Power consumption	W	10000
Frequency	Hz	50 / 60
Temperature	°C	650
Air flow (20°C)	l/min	1000
Pressure static	Pa	1200 (12 mbar)
Noise emission level LpA	dB	76
Size (L x W x H)	mm	390 x 132 x 215
Weight	kg	5.2 (with 10 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		



Plastic Welding > Hand tools > FORTE S3

ACCESSORIES