

TRIAC ST



To the product

Technical data

Article	141.227; 141.228; 141.230; 141.308; 141.309; 141.310; 141.311; 141.312; 144.013; 153.891	
Voltage	100 V; 120 V; 220 V; 230 V	
Frequency	50/60 Hz; 60 Hz	
Power	1500-1600 W	
Temperature	40-700 °C	104-1292 °F
Temperature setting stepless	Yes	
Airflow (20°C)	240 l/min	8.47 cfm
Stepless air volume adjustment	No	
Static pressure	3000 Pa	0.43 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in; M14	
Length	338 mm	13.3 in
Device diameter	90 mm	3.54 in
Handle diameter	56 mm	2.2 in
Weight	0.99 kg	2.18 lb
Power cable length	3 m	9.84 ft



TRIAC ST

Technical data

Plug	AU, 3 poles, 10A; CEE yellow, 3 poles, 16A; CH T11, 2 poles, 10A; CN, 2 poles, 10A; EU, 2 poles, 16A; JP, 2 poles, 15A; KR, 2 poles, 16A; UK, 3 poles, 13A; US, 2 poles, 15A, polarized
Noise emission level	67 dB (A)
Approvals	CE; KC; S+; cULus
Protection class	II
Approval number	MSIP-REM-Le1-TriacST
Country of origin	Switzerland

Scope of delivery

Tool case

Product items

141.227	TRIAC ST, 230V/1600W, EU plug
141.228	TRIAC ST, 120V/1600W, US plug
141.230	TRIAC ST, 100V/1500W, JP plug
141.308	TRIAC ST, 120V/1600W, CEE 3/16
141.309	TRIAC ST, 230V/1600W, UK plug
141.310	TRIAC ST, 230V/1600W, AU plug
141.311	TRIAC ST, 230V/1600W, CH plug
141.312	TRIAC ST, 230V/1600W, CN plug
144.013	TRIAC ST, 230V/1600W, M14, EU plug
153.891	TRIAC ST, 220V/1600W, KR plug