

TWINNY S



Especially well-suited for overhead welding in tunnel engineering. Combi-wedge welding machine with stepless adjustable temperature and drive.

- Easy operation
- Lightweight
- High welding speed
- Stepless adjustable temperature and drive
- Achieves perfect welding results, even under harsh environmental conditions, thanks to its hot air system.



SPECIFICATIONS

TWINNY S 100 V

Voltage	V~	100
Power consumption	W	1600
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Gearing		256 : 1 / 144 : 1
Speed	m/min	0.2 – 2.5 / 1.4 – 4
Welding pressure	N	max. 1000 / max. 500
Air flow (20°C)	l/min	Level 2: 150, Level 3: 190
Pressure static	Pa	Level 2: 1500 (15 mbar), Level 3: 2100 (21 mbar)
Noise emission level LpA	dB	71
Size (L x W x H)	mm	350 x 390 x 270
Weight	kg	6.5 - 6.9 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA

Plastic Welding > Welding machines > TWINNY S

Protection class II



TWINNY S 120 V

Voltage	V~	120
Power consumption	W	1900
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Gearing		256 : 1 / 144 : 1
Speed	m/min	0.2 – 2.5 / 1.4 – 4
Welding pressure	N	max. 1000 / max. 500
Air flow (20°C)	l/min	Level 2: 150, Level 3: 190
Pressure static	Pa	Level 2: 1500 (15 mbar), Level 3: 2100 (21 mbar)
Noise emission level LpA	dB	71
Size (L x W x H)	mm	350 x 390 x 270
Weight	kg	6.5 - 6.9 (with 3 m cord)

Marking of conformity



Approval mark



Certification scheme

CCA




Protection class II





TWINNY S 200 V

Voltage	V~	200
Power consumption	W	2200
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Gearing		256 : 1 / 144 : 1
Speed	m/min	0.2 – 2.5 / 1.4 – 4

Plastic Welding > Welding machines > TWINNY S

Welding pressure	N	max. 1000 / max. 500
Air flow (20°C)	l/min	Level 2: 150, Level 3: 190
Pressure static	Pa	Level 2: 1500 (15 mbar), Level 3: 2100 (21 mbar)
Noise emission level LpA	dB	71
Size (L x W x H)	mm	350 x 390 x 270
Weight	kg	6.5 - 6.9 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		

TWINNY S 230 V




Voltage	V~	230
Power consumption	W	2300
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Gearing		256 : 1 / 144 : 1
Speed	m/min	0.2 – 2.5 / 1.4 – 4
Welding pressure	N	max. 1000 / max. 500
Air flow (20°C)	l/min	Level 2: 150, Level 3: 190
Pressure static	Pa	Level 2: 1500 (15 mbar), Level 3: 2100 (21 mbar)
Noise emission level LpA	dB	71
Size (L x W x H)	mm	350 x 390 x 270
Weight	kg	6.5 - 6.9 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA

Plastic Welding > Welding machines > TWINNY S

Protection class II



TWINNY S 230 V


Voltage	V~	230
Power consumption	W	2900
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Gearing		256 : 1 / 144 : 1
Speed	m/min	0.2 – 2.5 / 1.4 – 4
Welding pressure	N	max. 1000 / max. 500
Air flow (20°C)	l/min	Level 2: 150, Level 3: 190
Pressure static	Pa	Level 2: 1500 (15 mbar), Level 3: 2100 (21 mbar)
Noise emission level LpA	dB	71
Size (L x W x H)	mm	350 x 390 x 270
Weight	kg	6.5 - 6.9 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		

ACCESSORIES




Test kit for welding fittings

110.051 - Test kit for welding fittings



Test kit with injector needle

110.052 - Test kit with injector needle



Welding fitting PE

106.950 - Welding fitting PE



Short Combiwedge

100.517 - Short Combiwedge, 50 mm with test channel

100.518 - Short Combiwedge, 50 mm without test channel



Long Combiwedge

100.525 - Long Combiwedge, 50 mm with test channel

100.526 - Long Combiwedge, 50 mm, without test channel



Air pressure test manometer with testing needle

142.475 -



Cross handle

112.974 -

