

UNIDRIVE 505



To the product



Technical data

Article	135.530; 135.531; 135.532	
Voltage	120 V; 230 V	
Frequency	50/60 Hz	
Power	1800-2300 W	
Temperature	100-560 °C	212-1040 °F
Speed	0.7-4.5 m/min	2.29-14.76 ft/min
Roll material	Silicone roller 50 shore A	
Welding nozzle / seam width	40 mm	1.18 in
Brushless drive motor	Yes	
Display	Yes	
Reversible drive	No	
Length	275 mm	10.82 in
Width	173 mm	6.81 in
Height	297 mm	11.69 in
Weight	4.5 kg	9.92 lb
Power cable length	3 m	9.84 ft
Plug	CEE blue, 3 poles, 16A; EU, 3 poles, 16A; US, 2 poles, 15A, polarized	
Noise emission level	70 dB (A)	
Approvals	CB Certification; CE; UKCA	
Protection class	I	
Country of origin	Switzerland	



UNIDRIVE 505

Scope of delivery

Cylinder brush, brass ø 15 mm; Allen wrench 3 mm; Welding plate; Tool case

Product items

135.530	UNIDRIVE 505, 230V/2300W, 40mm, EU plug
135.531	UNIDRIVE 505, 230V/2300W, 40mm, CEE 3/16
135.532	UNIDRIVE 505, 120V/1800W, 40mm, US plug