

UNIMAT V TAPE

For user-friendly, economical, fast strip welding with hot air.
For industrial fabrics or coated woven materials.

- High welding speed
- User-friendly
- Digital display of set and actual values of welding speed, temperature and air flow
- No corrective action required thanks to the new guide roller
- Steplessly controlled air flow
- Automatic start
- With tape unwind construction
- Simple rotatable handle



SPECIFICATIONS

UNIMAT Band 230 V

Voltage	V~	230
Power consumption	W	3680
Frequency	Hz	50 / 60
Temperature	°C	20 - 620
Speed	m/min	1.5 - 12
Air flow (20°C)	l/min	500
Air flow range	%	50 - 100
Pressure static	Pa	max. 5000 (50 mbar)
Noise emission level LpA	dB	70
Tape width	mm	40 or 50
Size (L x W x H)	mm	600 x 415 x 310
Weight	kg	28.0 (with 5 m cord and trolley attachment)

Marking of conformity



Approval mark





Plastic Welding > Welding machines > UNIMAT V TAPE

Certification scheme

CCA

Protection class I



ACCESSORIES

**Retrofit kit TAPE for UNIMAT V BAND**

115.014 - Retrofit kit TAPE 40 mm

115.015 - Retrofit kit TAPE 50 mm from OVERLAP to TAPE

**Band-Schweisseinheit 40 mm / 50 mm**

115.192 - Retrofit kit TAPE from 50 mm to 40 mm

115.193 - Retrofit kit TAPE from 40 mm to 50 mm

Andrückrolle 20 mm / 40 mm Keder with ball bearings

117.308 - Pressure roller 20 mm piping, with ball bearings

117.314 - Pressure roller 40 mm piping, with ball bearings