

UNIPLAN 510



To the product



Technical data

Article	177.403; 177.404; 177.406; 179.071; 179.072; 179.073; 179.077; 179.078; 179.079; 179.086; 179.087; 179.088; 179.090	
Frequency	50/60 Hz	
Speed	1-16 m/min	3.28-52.49 ft/min
Temperature	100-620 °C	212-1148 °F
Air volume adjustable	Yes	
LQS	No	
Brushless blower motor	Yes	
Length	500 mm	19.68 in
Width	310 mm	12.2 in
Height	300 mm	11.81 in
Weight	16 kg	35.27 lb
Power cable length	3 m	9.84 ft
Approvals	CB Certification; CE; UKCA	
Protection class	I	
Country of origin	Switzerland	

Scope of delivery

Hem and piping guide; Material lift-off device; Weight bracket base; Handle short; Handle bracket; Nozzle adjustment gauge; Wire brush, stainless steel; 2x Additional weight; Tool case



UNIPLAN 510

Product items

177.403	UNIPLAN 510, 230V/3450W, 40mm, CN 16(2P+PE)
177.404	UNIPLAN 510, 230V/3450W, 30mm, CN 16(2P+PE)
177.406	UNIPLAN 510, 230V/3450W, 20mm, CN 16(2P+PE)
179.071	UNIPLAN 510, 120V/1800W, 20mm, US plug
179.072	UNIPLAN 510, 120V/1800W, 30mm, US plug
179.073	UNIPLAN 510, 120V/1800W, 40mm, US plug
179.077	UNIPLAN 510, 230V/3450W, 20mm, CEE 3/16A UK
179.078	UNIPLAN 510, 230V/3450W, 30mm, CEE 3/16A UK
179.079	UNIPLAN 510, 230V/3450W, 40mm, CEE 3/16A UK
179.086	UNIPLAN 510, 230V/3450W, 40mm, EU plug
179.087	UNIPLAN 510, 230V/3450W, 30mm, EU plug
179.088	UNIPLAN 510, 230V/3450W, 20mm, EU plug
179.090	UNIPLAN 510, 230V/3450W, 40mm, w/o plug