

VARIANT 700 Series



Efficient welding of tarpaulins with the new VARIANT 700 series

The welding machines excels in versatility and efficiency. The 706/708's dual-nozzle system allows simultaneous welding from both sides. Featuring smart, one-touch operation for easy lift and weld functions, it ensures safety and precision. The 700's modular design effortlessly switches from overlap to spriegel welding, with a speed of up to 20 m/min, making it ideal for truck tarpaulin and tent production.



VARIANT 700 for overlap welding



VARIANT 702/704 for tape welding



VARIANT 706/708 for spriegel welding

VARIANT 700 Series

- Both sides at once welding, adjustable 80-400 mm
- Auto start/stop, material lift, nozzle in/out
- Dual antivandalism or reinforcing tapes welding
- Safe standing operation for better health/safety
- Modular, switches from overlap to spriegel or tape

Product items VARIANT 700 (for overlap welding)

VARIANT 700, 230V/3680W, 50mm, EU plug	176.859
VARIANT 700, 230V/3680W, 40mm, EU plug	176.860
VARIANT 700, 230V/3680W, 20mm, EU plug	176.861
VARIANT 700, 230V/3680W, 50mm, CEE 3/16	176.862
VARIANT 700, 230V/3680W, 40mm, CEE 3/16	176.863
VARIANT 700, 230V/3680W, 20mm, CEE 3/16	176.864
VARIANT 700, 400V/5500W, 50mm, CEE 5/16	176.865
VARIANT 700, 400V/5500W, 40mm, CEE 5/16	176.866
VARIANT 700, 400V/5500W, 20mm, CEE 5/16	176.867





Configure VARIANT 700

Product items VARIANT 702 (for reinforcement tape welding)

VARIANT 702, 230V/3680W, 50mm, EU plug	176.869
VARIANT 702, 230V/3680W, 50mm, CEE 3/16	176.870
VARIANT 702, 400V/5500W, 50mm, CEE 5/16	176.871



Configure VARIANT 702

Product items VARIANT 704 (for antivandalism tape welding)

VARIANT 704, 230V/3680W, 25mm, EU plug	176.873
VARIANT 704, 230V/3680W, 25mm, CEE 3/16	176.874
VARIANT 704, 400V/5500W, 25mm, CEE 5/16	176.875



Configure VARIANT 704

Product items VARIANT 706 (for spriegel welding)

VARIANT 706, 400V/11000W, 20mm, CEE 5/16

176.868



Configure
VARIANT 706

Product items VARIANT 708 (for double antivandalism tape welding)

VARIANT 708, 400V/11000W, 25mm, CEE 5/16

176.87



Configure VARIANT 708



