

## X84

Light hot air welding machine, which climbs even the steepest roofs at constant speed.

- Small, light and compact
- Also suitable for uneven surfaces
- Constant welding pressure
- Controlled welding speed
- Choice of two levels for air flow



### SPECIFICATIONS

#### X84 120 V

Voltage	V~	120
Power consumption	W	1900
Frequency	Hz	50 / 60
Temperature	°C	20 - 600
Speed	m/min	0.5 - 3.5
Welding pressure	N	250
Air flow (20°C)	l/min	Level 2: 150, Level 3: 190
Pressure static	Pa	Level 2: 1500 (15 mbar), Level 3: 2100 (21 mbar)
Noise emission level LpA	dB	67
Welding nozzle with	mm	30
Size (L x W x H)	mm	300 x 310 x 250
Weight	kg	6.1 (with 3 m cord)

Marking of conformity



Approval mark






Protection class II



#### X84 230 V

Voltage	V~	230
---------	----	-----




## Plastic Welding &gt; Welding machines &gt; X84

Power consumption	W	2900
Frequency	Hz	50 / 60
Temperature	°C	20 - 600
Speed	m/min	0.5 - 3.5
Welding pressure	N	250
Air flow (20°C)	l/min	Level 2: 150, Level 3: 190
Pressure static	Pa	Level 2: 1500 (15 mbar), Level 3: 2100 (21 mbar)
Noise emission level LpA	dB	67
Welding nozzle with	mm	30
Size (L x W x H)	mm	300 x 310 x 250
Weight	kg	6.1 (with 3 m cord)
Marking of conformity		
Approval mark		
Protection class II		

## X84 230 V

Voltage	V~	230
Power consumption	W	2300
Frequency	Hz	50 / 60
Temperature	°C	20 - 600
Speed	m/min	0.5 - 3.5
Welding pressure	N	250
Air flow (20°C)	l/min	Level 2: 150, Level 3: 190
Pressure static	Pa	Level 2: 1500 (15 mbar), Level 3: 2100 (21 mbar)
Noise emission level LpA	dB	67
Welding nozzle with	mm	30
Size (L x W x H)	mm	300 x 310 x 250

## Plastic Welding &gt; Welding machines &gt; X84

Weight	kg	6.1 (with 3 m cord)
Marking of conformity		
Approval mark		
Protection class II		



Plastic Welding > Welding machines > X84

---

## ACCESSORIES